

Innovation
for A Better Life

COSLINK **ESS**

**CHANGE
YOUR ENERGY
PROVIDE
ENERGY
INDEPENDENCE**

EnerMax-C&I

Distributed Active Control Energy Storage Cabinet

www.coslinkess.com

Official Authorized ESS Integrator of CATL



Features and Advantages



Highly integrated

- Cluster-level active control
- Support of stacking and expansion installation
- Simplified after-sales operation and maintenance



Security

- Local EMS real-time monitoring
- Built-in aerosol firefighting system
- Reserved water firefighting interface
- IEC62619



Smart

- Distributed deployment
- Support of peak shifting
- Support of parallel connection & flexible management

Leader of ESS Active Control Technology

Provide Professional OEM/ODM Solution and Product



UN38.3

Model	CB215-0.5C
Nominal Capacity [Ah]	280 (25°C@ 0.5C discharge)
Nominal Voltage [V]	768
Nominal Energy [kWh]	215
Max. Discharge Depth	≤ 90%
Max. Continuous Charge Current [A]	140 (0.5C)
Charge Cut-Off Voltage [V]	852
Max. Continuous Discharge Current [A]	140 (0.5C)
Discharge Cut-Off Voltage [V]	696
Dimensions [W*D*H, mm]	1500*950*2300
Charging Temperature Range [°C]	0 to 45
Discharging Temperature Range [°C]	-20 to +60
Optimal Operating Temperature Range [°C]	20 to 30
Storage Humidity	60 ± 25% RH (non-condensing)
Cooling	Forced air cooling
Communication	CAN2.0, RS485
Weight [kg]	~1950
IP Grade	IP54
Fire-Proof	Aerosol

Note: The above information may subject to update without prior notice.